	FOR OFFICIAL USE				
_					
	National				
	Qualification 2017	ns		Mar	k

X735/76/01

Graphic Communication

WEDNESDAY, 10 MAY 1:00 PM – 3:00 PM



orename(s) Surname				Full name of centre						
	Number of sea			 ame	Sur			rename(s)		
Date of birth							1	Date of birtl		

Total marks — 70

Attempt ALL questions.

All dimensions are in mm.

All technical sketches and drawings use third angle projection.

You may use rulers, compasses or trammels for measuring.

In all questions you may use sketches and annotations to support your answer if you wish.

Write your answers clearly in the spaces provided in this booklet. Additional space for answers is provided at the end of this booklet. If you use this space you must clearly identify the question number you are attempting.

Use blue or black ink.

Before leaving the examination room you must give this booklet to the Invigilator; if you do not, you may lose all the marks for this paper.



1. A CAD technician created a 3D model of the bicycle, shown below.




(a)

Describe, giving two reasons, how the 3D CAD model can be used to support manufacture through testing.

(continued)

MARKS DO NOT WRITE IN THIS MARGIN

(b) A new brake disc design was requested for the bicycle.



Shape A was to be repeated 60 times. State the CAD edit that would be used to create the feature.

1




Page 03

(continued)

MARKS DO NOT WRITE IN THIS MARGIN

(c) The bicycle uses a spring as part of the suspension system, shown below.



The spring was modelled as a separate component using 3D CAD.

Describe the 3D CAD technique used to model the spring.

You must make reference to the dimensions above.


You may use sketches to illustrate your answer.



3



Page 04



(d) The handlebars were 3D CAD modelled as a single component. Describe the modelling technique used to generate the component. You may use sketches to illustrate your answer.

2

Rubber handles were required to cover the handlebars.

The CAD technician used top down modelling to create the rubber handles.

(e)	Describe	two	advantages	of	top	down	modelling	in	relation	to	these	
	compone	nts.										2





1. (continued)

DO NOT WRITE IN THIS MARGIN

(f) The shape of the rubber handle was sketched prior to being modelled using 3D CAD.

The orthographic sketch of the rubber handle is shown below.







Page 06

1.	(f)	(continued)	MARKS	WRITE IN THIS
		Describe the 3D CAD technique used to model the rubber handle with reference to the dimensions in the sketch of the handle (shown opposite).	6	MARGIN
		You may use sketches to illustrate your answer.		



Page 07

1. (continued)

(g) Two sectional views of the bicycle crank are shown below.




Figure 1

Figure 2

(i) State the type of sectional view shown in Figure 1.

1

(ii) State the type of sectional view shown in Figure 2.

1

[Turn over for next question

DO NOT WRITE ON THIS PAGE



Page 09

2. Graphics 1 and 2 are both used within the building industry and serve different purposes.



Graphic 1

Graphic 2

- (a) State the intended user and explain the purpose of each graphic.
 - (i) Graphic 1

2

User _____

Purpose _____

(ii) Graphic 2 2

User _____

Purpose _____

Page 10

2. (continued)

MARKS DO NOT WRITE IN THIS MARGIN

(b) A construction company uses CAD software that makes use of **cloud computing**. The company engineers visit construction sites on a regular basis and require access to the most current CAD data.

(i)	Describe two advantages that cloud computing can offer the construction company.
(ii)	Describe two disadvantages of cloud storage .
()	

3. A layout from a health magazine is shown below.



(a) The graphic designer has used **emphasis** in the layout shown above. Describe how each of these items has been emphasised.

(i)	The pull quote.	,
(ii)	The body text.	1
(iii)	The photograph of the model.	

3. (continued)

MARKS DO NOT WRITE IN THIS MARGIN

(b)	Explain, giving two reasons, why the graphic designer has limited the use of colour in the layout.	2
(c)	Describe the effect of using both serif and sans serif fonts in this layout.	1
d)	The title is in a serif typeface which the graphic designer felt was suitable for use in the layout.	
	Explain why this is a suitable typeface for this layout.	1
e)	Describe how the graphic designer has created rhythm in the layout.	1
f)	Describe how the graphic designer has created texture in the layout.	1
g)	Describe how the graphic designer has used value in the layout.	1



DO NOT WRITE IN THIS MARGIN

4. A graphic designer for a sports magazine created Layout 1 as a draft idea for a basketball article.

The magazine editor suggested DTP features to create better visual impact.

The graphic designer then produced a second draft, Layout 2.



Layout 1



Layout 2



(i)	(A) Feature	1
	(B) Reasons	
(ii)	(A) Feature	1
	(B) Reasons	
(iii)	(A) Feature	1
	(B) Reasons	
(iv)	(A) Feature	1
	(B) Reasons	2



(continued)

1

2

MARKS DO NOT WRITE IN THIS MARGIN

(b) High-resolution images used in the magazine were downloaded from a photo stock website for a small cost.

(i)	Explain what is meant by the term high-resolution.

(ii) State the name of a suitable file type for an image.



(c) Prior to paying for the high-resolution images, low-resolution samples were available to download for free. These images contained watermarks, as shown above.

Explain, giving two reasons, why watermarks are added to the free images.

[Turn over for next question


DO NOT WRITE ON THIS PAGE



Page 17

5. A packaging proposal is shown below.

DO NOT WRITE IN THIS MARGIN






Page 18


MARKS DO NOT WRITE IN THIS MARGIN


1


(continued) 5.

(a) Indicate the correct **auxiliary view** by ticking (✓) a box below. Use a ruler, trammel or compasses to measure.












Page 19


(continued)

MARKS DO NOT WRITE IN THIS MARGIN

(b) The orthographic drawing of the packaging is shown below. The packaging will have different information on various faces.



Indicate the position of faces A-F on the surface development below. 6 The surface development is shown from the outside.






Page 20

6

6. A CAD technician created a 3D model and technical drawing of an oil pump.

Use the exploded view and parts list on the **Supplementary Sheet for use**with **Question 6**, provided, to answer this question.



SECTION A-A

- (a) Complete Section A–A above by applying hatching lines to appropriate areas in accordance to British Standard conventions.
- (b) Add the part number of the three components indicated on Section A–A above.

[END OF QUESTION PAPER]



MARKS DO NOT WRITE IN THIS MARGIN

ADDITIONAL SPACE FOR ANSWERS



Page 22

MARKS DO NOT WRITE IN THIS MARGIN

ADDITIONAL SPACE FOR ANSWERS



Page 23

[BLANK PAGE]

DO NOT WRITE ON THIS PAGE

Acknowledgement of Copyright

Question 2 Nikonaft/shutterstock.com

marina_ua/shutterstock.com

Question 3 Casey K. Bishop/shutterstock.com

ElenaGaak/shutterstock.com 13Imagery/ shutterstock.com One AND only/shutterstock.com

ORLIO/shutterstock.com

Irina Bg/shutterstock.com

Question 4 Eugene Onischenko/shutterstock.com

Eugene Onischenko/shutterstock.com



Page 24



X735/76/11


Graphic Communication Supplementary Sheet


WEDNESDAY, 10 MAY 1:00 PM - 3:00 PM


Supplementary Sheet for use with Question 6.

















END ELEVATION

DRAWII	NG TITLE	ASSEMBLY
QUESTIC	ON TITLE	OIL PUMP
	COURSE	HIGHER GRAPHIC COMMUNICATION
DATE		V/201
SCALE	NTS	\times SQA (\oplus)
SHEET	1/1	ALL SIZES IN MM DO NOT SCALE

[BLANK PAGE]

DO NOT WRITE ON THIS PAGE